

Application No. 10/650,058
Response to Office Action

Customer No. 01933

Listing of Claims:

1. (Currently Amended) An optical deflection device
comprising:

(a) a rotary unit comprising a rotary polygon mirror and a
magnet;

5 (b) a dynamic pressure bearing comprising a rotary bearing
member for rotatably supporting the rotary unit and a fixed
bearing member for engaging with the rotary bearing member;

(c) a stator unit comprising a base member for supporting
the fixed bearing member and a magnet coil for driving the rotary
10 unit in cooperation with the magnet; and

(d) a stabilizing member provided on an upper portion of the
base member and in ~~the~~ a vicinity of an outer circumference of
the polygon mirror ~~for stabilizing to stabilize~~ air flow
generated by a rotation of the polygon mirror,

15 wherein the stabilizing member has a height greater than
~~that~~ a height of a lower surface of the rotary polygon mirror;
and

wherein the stabilizing member is provided in an area on a
side of the polygon mirror between the polygon mirror and a side
20 wall of a main body of the optical scanning apparatus.

Claim 2 (Canceled).

Application No. 10/650,058
Response to Office Action

Customer No. 01933

3. (Currently Amended) An optical scanning apparatus comprising:

(a) a main body;

(b) an optical deflection device provided in the main body,
5 said optical deflection device comprising a rotor unit having
including a rotary polygon mirror, a dynamic pressure bearing for
rotatably supporting the rotor unit, and a stator unit having
including a base member for supporting the dynamic pressure
bearing;

10 (c) an optical member of a scanning optical system provided
in the main body; and

(d) a stabilizing member provided in ~~the~~ a vicinity of an
outer circumference of the polygon mirror inside the main body
for ~~stabilizing~~ to stabilize air flow generated by a rotation of
15 the polygon mirror;

wherein the stabilizing member has a height greater than a
height of a lower surface of the rotary polygon mirror; and

wherein the stabilizing member is provided in an area on a
side of the polygon mirror between the polygon mirror and a side
20 wall of the main body of the optical scanning apparatus.

Claims 4 and 5 (Canceled).